

# 3 Ton Double Axle Pneumatic Service Trailer



The versatile service trailer is equipped with a diesel compressor delivering 6.5 bar of pressure to drive the reliable double diaphragm type fluid pumps.

The air is cleaned, lubricated and pressure regulated through an onboard FRL before being delivered to the fluid pumps.

4x 300 litre Polyethylene Tanks give the trailer a total fluid capacity of 1200 litres which can be configured to carry various fluids to suit the specific application.

Tanks are set as low as possible in the steel frame to ensure stability at highway speeds and reduce roll over risk on rough terrain.

Up to 4 different fluids can be carried on this phenomenal piece of equipment.

The hose reel compartment is fully enclosed and fitted with lockable aluminium doors.

The pneumatic pumps deliver a flow rate of up to 12 litre per minute for hydraulic oil.  
(flow rates are affected by viscosity of the product)

Tanks are manually filled through easily accessible lids or optional refill couplers can be specified to ensure a true closed loop refill operation.



Spring return hose reels ensure safe and easy retractable 15m hoses while keeping things nice and tidy while travelling.

To ensure minimum environmental impact, a drip tray is conveniently located below the nozzles to minimize contamination & spillage.

The trailer has a GVM of 2500 kg.



### Products:

Diesel driven compressor

- 2x fluids (600ltr each)\*
- 1x grease (manual pump)
- 1x air (6.5 Bar)

\*pneumatic pumps deliver optimal flow

\*can be configured for 4 products

### Additional features:

- Two Fire Extinguishers
- Spare wheel
- Jockey wheel
- Reflective tape

Tel: 079 884 0632  
Fax: 086 648 5216  
Email: [sales@tankkraft.co.za](mailto:sales@tankkraft.co.za)  
Reg. No. 2015/343535/07  
VAT No: 4370279780

18 & 20 Arnhem Crescent  
Die Heuwel, Witbank  
P.O. Box 8744  
Die Heuwel  
Witbank, 1042

